



# Installation Manual

## CuratOR<sup>®</sup> EX3242

Color LCD Monitor

### Important

Please read this “Installation Manual”, and “Instructions for Use” (separate volume) carefully to familiarize yourself with safe and effective usage.

- 
- Refer to the “Instructions for Use” for information on the installation / connection of the monitor.
-

This product has been adjusted specifically for use in the region to which it was originally shipped.  
If operated outside this region, the product may not perform as stated in the specifications.

---

No part of this manual may be reproduced, stored in a retrieval system, or transmitted, in any form or by any means, electronic, mechanical, or otherwise, without the prior written permission of EIZO Corporation. EIZO Corporation is under no obligation to hold any submitted material or information confidential unless prior arrangements are made pursuant to EIZO Corporation's receipt of said information. Although every effort has been made to ensure that this manual provides up-to-date information, please note that EIZO product specifications are subject to change without notice.

---

# Contents

<b>Contents.....</b>	<b>3</b>
<b>Chapter 1 Basic Adjustment / Setting .....</b>	<b>4</b>
1-1. Loading the Monitor Settings.....	4
● Saving current settings to “User1” through “User5”.....	5
1-2. Switching Input Signals .....	5
1-3. Using Custom Keys .....	6
● Setting a function to custom keys .....	6
1-4. Locking Control Buttons.....	6
<b>Chapter 2 Advanced Adjustment / Setting .....</b>	<b>7</b>
2-1. Basic Operation of the Setting Menu .....	7
2-2. Setting Menu Functions .....	9
● Color.....	9
● Signal .....	10
● Preferences .....	11
● Information .....	13
● PbyP .....	14
● PinP .....	15
<b>Chapter 3 Troubleshooting.....</b>	<b>16</b>
3-1. No Picture Displayed.....	16
3-2. Imaging Problems.....	17
3-3. Other Problems .....	17
<b>Chapter 4 Reference .....</b>	<b>18</b>
4-1. Main Default Settings .....	18
4-2. Pin Specifications .....	19
<b>Appendix.....</b>	<b>20</b>
Trademark .....	20
License .....	20
LIMITED WARRANTY.....	21
Recycling Information .....	22

# Chapter 1 Basic Adjustment / Setting

This chapter describes the basic functions that can be adjusted and set by pressing the buttons on the bottom of the monitor.

## 1-1. Loading the Monitor Settings


Basic settings are made in advance at the factory.

It is possible to switch to the following preset settings that have been set in advance.

DisplayPort [sRGB]	Basic settings for DisplayPort when displaying the color gamut in sRGB. The input signal is set to DisplayPort and the color gamut to sRGB when this item is selected. Settings cannot be changed. For information about the main default settings, see “ <a href="#">4-1. Main Default Settings</a> ” (page 18).
DisplayPort [BT.2020]	Basic settings for DisplayPort when displaying the color gamut in BT.2020. The input signal is set to DisplayPort and the color gamut to BT.2020 when this item is selected. Settings cannot be changed. For information about the main default settings, see “ <a href="#">4-1. Main Default Settings</a> ” (page 18).
HDMI [BT.2020]	Basic settings for HDMI. The input signal is set to HDMI when this item is selected. Settings cannot be changed. For information about the main default settings, see “ <a href="#">4-1. Main Default Settings</a> ” (page 18).
SDI [BT.2020]	Basic settings for SDI. The input signal is set to SDI 1 when this item is selected. Settings cannot be changed. For information about the main default settings, see “ <a href="#">4-1. Main Default Settings</a> ” (page 18).
“User1” through “User5”	You can save the current setting values and display status in the following items. These items are not selectable unless they have been saved. For details, see “ <a href="#">Saving current settings to “User1” through “User5”</a> ” (page 5).

### 1. Press (PRESET).

The preset menu is displayed.



### 2. Press to select the item to load, and then press (ENTER).

The pre-made settings are loaded and the settings are changed.

#### Note

- The preset menu will disappear after about 10 seconds have elapsed if no operation is performed.

## ● Saving current settings to “User1” through “User5”

You can save the current setting values and display status to “User1” through “User5”.

### 1. Press (MENU).

The Setting menu appears.

### 2. Press (F3) or (F4) to select “Preferences”, and then press (ENTER).

The “Preferences” menu appears.

### 3. Press (F3) or (F4) to select “Preset Save”, and then press (ENTER).

The “Preset Save” menu appears.

### 4. Press (F3) or (F4) to select one from “User1” to “User5”, and then press (ENTER).

The confirmation screen appears.

### 5. Press (F3) or (F4) to select “OK”, and then press (ENTER).


Current setting values and display status will be saved in the selected item.

## 1-2. Switching Input Signals

Select the signal input to the monitor and display it on the screen.

### 1. Press (INPUT).

The input port menu appears.



### 2. Press ( ) to select an input signal.

This switches to the selected input signal.

### 3. Press (INPUT).

This exits the menu screen.

#### Note

- If you press (INPUT) while the input port menu is displayed in dual screen mode (PbyP or PinP), the “PbyP” / “PinP” menu is displayed. For details, see “PbyP” (page 14) and “PinP” (page 15).
- After the input port menu is displayed, the input port menu will disappear after 10 seconds if no key operations are performed.
- After 60 seconds with no signal input, the monitor backlight will turn off and it will enter power saving mode.

## 1-3. Using Custom Keys

Execute the functions assigned to the custom keys (F1 (  $\leftarrow$  ), F2 (  $\rightarrow$  ), F3 (  $\downarrow$  ) and F4 (  $\uparrow$  )). For information on how to set a function to each custom key, see “[Setting a function to custom keys](#)” (page 6).

### 1. Press F1 ( $\leftarrow$ ), F2 ( $\rightarrow$ ), F3 ( $\downarrow$ ) and F4 ( $\uparrow$ ).

The function associated with the custom key that is pressed will run.

**Note**

- For dual screen display (PbyP or PinP), adjust the “Active Window” side.

### ● Setting a function to custom keys

#### 1. Press $\equiv$ (MENU).

The Setting menu appears.

#### 2. Press $\downarrow$ (F3) or $\uparrow$ (F4) to select “Preferences”, and then press $\blacktriangleright$ (ENTER).

The “Preferences” menu appears.

#### 3. Press $\downarrow$ (F3) or $\uparrow$ (F4) to select “Custom Key”, and then press $\blacktriangleright$ (ENTER).

The “Custom Key” menu appears.

#### 4. Press $\downarrow$ (F3) or $\uparrow$ (F4) to select which custom key to set the function to, and then press $\blacktriangleright$ (ENTER).

#### 5. Press $\downarrow$ (F3) or $\uparrow$ (F4) to select the function, and then press $\blacktriangleright$ (ENTER).

The selected function is assigned to the corresponding custom key.

## 1-4. Locking Control Buttons

Adjusted or set states can be made unchangeable.

**Procedure**

1. Press the  $\equiv$  (MENU) and  $\blacktriangleright$  (ENTER) keys for at least 4 seconds.

**Note**

- Press the  $\equiv$  (MENU) and  $\blacktriangleright$  (ENTER) keys for at least 4 seconds to exit Key Lock.


# Chapter 2 Advanced Adjustment / Setting

This chapter describes advanced monitor adjustment and setting procedures using the main menu.


## 2-1. Basic Operation of the Setting Menu

### 1. Menu display

1. Press  (MENU).



The Setting menu appears.



## 2. Adjustment / Setting

Pressing  (MENU) during adjustment/setting will cancel the adjustment/setting and restore the state prior to making changes.

1. Press  (F3) or  (F4) to select a menu to adjust/set, and then press  (ENTER).  
The submenu appears.



2. Press  (F3) or  (F4) to select an item to adjust/set, and then press  (ENTER).  
The Adjustment/Setting menu appears.



3. Press  (F1) or  (F2) to adjust/set the selected item, and then press  (ENTER) to confirm the settings.  
The submenu appears.

## 3. Exiting

1. Press  (MENU).  
The Setting menu appears.
2. Press  (MENU).  
Exits the Setting menu.


## 2-2. Setting Menu Functions

### ● Color

Color (All)		
Active Window	[	All ]
Backlight	[	100 ]
Brightness	[	0 ]
Contrast	[	100 ]
Temperature	[	6500K ]
Gamma	[	2.4 ]
Color Gamut	[	sRGB ]
Hue	[	0 ]
Saturation	[	0 ]
Gain	[	0 ]

Function	Setting	Description
Active Window	PbyP	Left Window / Right Window Select which window to adjust settings when using dual screen display (PbyP or PinP). Disabled during single screen display. <b>Note</b> <ul style="list-style-type: none"><li>For dual screen display (PbyP or PinP), color adjustment can be performed for each screen selected in "Active Window".</li></ul>
	PinP	Large Window / Small Window
	Single	All
Backlight	0 to 100	Adjust screen brightness by changing the brightness of the backlight (light source from the LCD back panel). <b>Note</b> <ul style="list-style-type: none"><li>The backlight is disabled when the right window or small window is selected during PbyP or PinP.</li></ul>
Brightness	0 to 100	Adjust the brightness of black.
Contrast	0 to 100	Contrast can be adjusted. Adjust the brightness of the screen by changing the video signal level.
Temperature	Native / 6500K / 9300K / User	Adjust the color temperature. The color temperature is normally used to express the hue of "White" and / or "Black" with a numerical value. The value is expressed in degrees "K" (Kelvin). The screen becomes reddish at low color temperatures and bluish at high color temperatures, similar to the temperatures of a flame. <b>Note</b> <ul style="list-style-type: none"><li>Select "Native" to display the original colors of the LCD panel.</li><li>"Gain" allows you to perform more advanced adjustment. When gain is changed, "Temperature" is changed to "User".</li><li>The gain preset values are set for each color temperature setting value.</li></ul>
Gamma	1.8 / 2.0 / 2.2 / 2.4 / 2.6 / DICOM / HLG / PQ	Adjust the gamma. While the brightness of the monitor varies depending on the video level of the input signal, the variation rate is not proportional to the input signal. Maintaining the balance between the input signal and brightness of the monitor is referred to as "Gamma correction".
Color Gamut	Native / sRGB / BT.2020	Set the color reproduction area (color gamut). The color gamut is the range of colors that can be represented. Multiple standards are defined. <b>Note</b> <ul style="list-style-type: none"><li>Select "Native" to display the original color gamut of the LCD panel.</li></ul>
Hue	-100 to 100	Adjust the hue.
Saturation	-100 to 100	Adjust the color saturation.
Gain	0 to 255	The brightness of each color component (red, green, and blue) is called "gain". The hue of "white" can be changed by adjusting the gain.


## ● Signal



Function	Setting	Description
Active Window	(In single screen display mode.) All (When "Multi Window" is set to "PbyP") Left Window / Right Window (When "Multi Window" is set to "PinP") Large Window / Small Window	Select which window to adjust settings in during dual screen display (PbyP or PinP). Disabled during single screen display.
Input Color Format <sup>*1</sup>	(When input signal is DisplayPort.) Auto / YUV / RGB (When input signal is HDMI.) Auto / YUV 4:2:2 / YUV 4:4:4 / RGB (When input signal is SDI.) Auto / YCC4:2:2 10bit / YCC4:2:2 12bit / YCC4:4:4 10bit / YCC4:4:4 12bit / RGB4:4:4 10bit / RGB4:4:4 12bit	The color space of the input signal can be specified. Try changing this setting if colors are not displayed correctly. Normally, select "Auto". When an SDI signal is input, the bit depth is specified using the "Input Color Format". If the specified bit depth is invalid, a signal error is displayed.
YUV Color Matrix <sup>*1</sup>	Auto / BT.601 / BT.709 / BT.2020	Select the YUV format of the input signal. Use this setting for gradation collapse or other occurrences where the screen is displayed incorrectly because of a problem with the input signal.
Input Range	(When input signal is DisplayPort or HDMI.) Auto / Full / Limited (When input signal is SDI or DVI.) Full / Limited	Depending on the video reproduction device, there may be a restriction on black and white video signal levels output to the monitor. This kind of signal is called "Limited range". On the other hand, unlimited signals are called "Full range". <ul style="list-style-type: none"> <li>• "Auto" Input signal brightness range is automatically judged and is displayed appropriately (recommended setting). Depending on the video reproduction device, Limited range and Full range may not be able to be judged by the monitor. In such a case, selecting "Full" or "Limited" will allow it to be displayed appropriately.</li> <li>• "Full" To be selected in case of Full range signals. Appropriate display can be obtained when this is selected, in case both blacks and whites are corrupted.</li> <li>• "Limited" To be selected in case of Limited range signals. When this is selected, the output signal range is expanded from 0 to 255 to obtain an appropriate display when black is pale and white is dull.</li> </ul>

\*1 Disabled when input signal is DVI.

## ● Preferences



Function	Setting	Description
Multi Window	Single / PbyP / PinP	<p>Select single screen display or dual screen display (PbyP or PinP). Disabled when “Display Direction” is set to “180°” or “Mirror”.</p> <ul style="list-style-type: none"> <li>“Single” Displays the selected input signal on the screen.</li> <li>“PbyP” Displays two different signals side-by-side on one screen simultaneously.</li> <li>“PinP” Displays two different signals on one screen by overlapping a subscreen on a main screen.</li> </ul> <p><b>Note</b></p> <ul style="list-style-type: none"> <li>In PbyP and PinP, the same input signal can be displayed on two screens. Example: During PbyP display, select “DisplayPort” for both “Left Window” and “Right Window” in the “PbyP” screen.</li> <li>“SDI 1” and “SDI 2” cannot be displayed simultaneously.</li> </ul>
Display Direction <sup>*1</sup>	Normal / 180° / Mirror	<p>Select the rotation angle or horizontally flip the main screen.</p> <p><b>Note</b></p> <ul style="list-style-type: none"> <li>Displays  on the screen when “180°” selected.</li> <li>Displays  on the screen when “Mirror” selected.</li> </ul>
Languages	English / German / French / Spanish / Italian / Swedish / Japanese / Simplified Chinese / Traditional Chinese / Russian / Portuguese	Select the language to be used for display in settings and all menus.
PRESET Save	User1 User2 User3 User4 User5	<p>Save current setting values and display status for each user.</p> <p><b>Note</b></p> <ul style="list-style-type: none"> <li>The saved items are the same as the presets (DisplayPort [sRGB], DisplayPort [BT.2020], HDMI [BT.2020], SDI [BT.2020]). For the setting items of preset settings, see “4-1. Main Default Settings” (page 18).</li> </ul>
Custom Key	[F1] [F2] [F3] [F4]	<p>Off / Backlight / Gamma / Color Gamut / Multi Window / Display Direction / Swap</p> <p>Select the function that is assigned to each custom key. For details, see “Setting a function to custom keys” (page 6).</p>


Function		Setting		Description
Advanced Setting	Auto Input Detection <sup>*1</sup>	On / Off		<p>This function automatically recognizes the connector through which computer signals are input, and displays images on the screen accordingly.</p> <ul style="list-style-type: none"> <li>“On” When the monitor is connected to multiple devices, if a specific device enters power saving mode or no signals are input to the monitor, the connector is automatically changed to another one to which signals are input.</li> <li>“Off” Set to this when manually selecting input signals. In this case, you can select the input signal to display using the  control button on the bottom of the monitor. For details, see “<a href="#">1-2. Switching Input Signals</a>” (page 5).</li> </ul> <p><b>Note</b></p> <ul style="list-style-type: none"> <li>When this function is set to “On”, the monitor only enters the power saving mode when signals are not input from any device.</li> </ul>
	Input Skip <sup>*1</sup>	DisplayPort HDMI SDI 1 SDI 2 DVI	- / Skip	<p>When “Auto Input Detection” is “On”, select the port to skip signal detection.</p> <p><b>Note</b></p> <ul style="list-style-type: none"> <li>If all of the ports are set to “Skip”, then input signal will not be detected, in the same way as when “Auto Input Detection” is set to “Off”.</li> </ul>
	On-Screen Logo	On / Off		Select whether to display or hide the logo when the monitor starts.
	SDI 1 Input equalizer	On / Off		<p>Corrects the SDI 1 input signal</p> <p><b>Note</b></p> <ul style="list-style-type: none"> <li>If noise is apparent when using the short SDI cable, set this to “Off”.</li> </ul>
	RS-232C	19200 bps / 115200 bps		Sets the communication speed when controlling this product from an external device connected using the RS-232C terminal.
Monitor Reset		OK / Cancel		Restores all settings to their default values.

<sup>\*1</sup> Disabled during dual screen display (PbyP or PinP).

## ● Information


Display the monitor information (model name, serial number (S/N), usage time) and the input signal information.

**Example:**



## ● PbyP


If you press  (INPUT) while in PbyP dual screen mode, the “PbyP” menu is displayed.



Function	Setting	Description
Left Window	DisplayPort / HDMI / SDI 1 / SDI 2 / DVI	Select the signal input to the left window when PbyP dual screen display. <b>Note</b> <ul style="list-style-type: none"><li>• “SDI 1” and “SDI 2” cannot be displayed simultaneously.</li></ul>
Right Window	DisplayPort / HDMI / SDI 1 / SDI 2 / DVI	Select the signal input to the right window when PbyP dual screen display. <b>Note</b> <ul style="list-style-type: none"><li>• “SDI 1” and “SDI 2” cannot be displayed simultaneously.</li></ul>
Swap		Swap the input ports of left window and right window. <b>Note</b> <ul style="list-style-type: none"><li>• Swapping may not be possible for some input signals.</li></ul>

## ● PinP


If you press  (INPUT) while in PinP dual screen mode, the “PinP” menu is displayed.



Function	Setting	Description
Large Window	DisplayPort / HDMI / SDI 1 / SDI 2 / DVI	Select the signal input to the large window when PinP dual screen display. <b>Note</b> <ul style="list-style-type: none"><li>“SDI 1” and “SDI 2” cannot be displayed simultaneously.</li></ul>
Small Window	DisplayPort / HDMI / SDI 1 / SDI 2 / DVI	Select the signal input to the small window when PinP dual screen display. <b>Note</b> <ul style="list-style-type: none"><li>“SDI 1” and “SDI 2” cannot be displayed simultaneously.</li></ul>
PinP Size	Small / Large	Select size of the small window.
PinP Position	Upper Right / Lower Right / Lower Left / Upper Left	Select position of the small window.
Swap		Swaps the input ports of the large window and small window. <b>Note</b> <ul style="list-style-type: none"><li>Swapping may not be possible for some input signals.</li></ul>

# Chapter 3 Troubleshooting

## 3-1. No Picture Displayed

Problem	Possible cause and remedy
<b>1. No picture.</b>	<ul style="list-style-type: none"><li>Check whether the power cord is connected properly.</li><li>Check whether the DC OUT terminal and the DC IN terminal are connected properly.</li><li>Turn on the power switch.</li><li>Check whether the main power indicator of the AC adapter is on.</li><li>Turn off the power and then turn it on again.</li></ul>
<b>2. The message below appears.</b>  • This message appears when no signal is input. Example:  A dark gray rectangular screen with white text that reads "DisplayPort" on top and "No Signal" below it.  • This message indicates that the input signal is outside the specified frequency range. Example:  A dark gray rectangular screen with white text that reads "DisplayPort" on top and "Signal Error" below it.	These messages appear when the signal is not input correctly even though the monitor is functioning properly.  <ul style="list-style-type: none"><li>The message shown on the left may appear, because some devices to be connected do not output the signal immediately after power-on.</li><li>Check whether the device to be connected is turned on.</li><li>Check whether the signal cable is connected properly.</li><li>Turn off the power and then turn it on again.</li><li>Change the setting for "Auto Input Detection" under "Advanced Setting" in the "Preferences" menu to "Off" and then manually switch the input signals (see <a href="#">"Auto Input Detection*1" (page 12)</a>).</li><li>Check whether the device to be connected is configured to meet the resolution and vertical scan frequency requirements of the monitor.</li><li>Reboot the device to be connected.</li></ul>

## 3-2. Imaging Problems

Problem	Possible cause and remedy
<b>1. The screen is too bright or too dark.</b>	<ul style="list-style-type: none"><li>Use "Brightness" or "Backlight" in the Setting menu to adjust it.</li></ul>
<b>2. Text is blurred</b>	<ul style="list-style-type: none"><li>Check whether the connected device is configured to meet the resolution and vertical scan frequency requirements of the monitor (see "Displayable Input Signals" in the User's Manual).</li></ul>
<b>3. Afterimages appear</b>	<ul style="list-style-type: none"><li>Afterimages are particular to LCD monitors. Avoid displaying the same image for a long time.</li><li>Use the screen saver or power saving function of the connected device to avoid displaying the same image for extended periods of time.</li><li>An afterimage may appear even after a short time period has elapsed depending on the displayed image. If this occurs, changing the image or leaving the power off for a few hours may solve the problem.</li></ul>
<b>4. Green, red, blue, white dots or dark dots remain on the screen</b>	<ul style="list-style-type: none"><li>This is due to LCD panel characteristics and not a malfunction.</li></ul>
<b>5. The screen suddenly went black. / The screen does not become brighter after increasing the "Backlight" value in the Settings menu.</b>	<ul style="list-style-type: none"><li>This product is equipped with a heat dissipation fan. If the fan is not operating properly, screen brightness can be limited in order to lower the internal temperature. In this case, please make sure that the fan is operating properly.</li></ul>

## 3-3. Other Problems

Problem	Possible cause and remedy
<b>1. The Setting menu does not appear.</b>	<ul style="list-style-type: none"><li>Make sure the lock function is not set to "On." (See "<a href="#">1-4. Locking Control Buttons</a>" (page 6).)</li></ul>
<b>2. The message below appears.</b> <ul style="list-style-type: none"><li>This will be displayed when a 6-bit (64 gradient) signal is being input. Example: </li></ul>	<p>This will be displayed when the signal is not displaying properly.</p> <ul style="list-style-type: none"><li>Turn off the power to the connected device and this product and then turn on the power again.</li><li>Check the settings on the connected device.</li></ul>

# Chapter 4 Reference

## 4-1. Main Default Settings

### Preset


Item		Default			
		DisplayPort [sRGB]	DisplayPort [BT.2020]	HDMI [BT.2020]	SDI [BT.2020]
Input Port	MAIN (Left Window / Large Window)	DisplayPort	DisplayPort	HDMI	SDI 1
	SUB (Right Window/Small Window)	SDI 1	SDI 1	SDI 1	DVI
Preferences	Multi Window	Single	Single	Single	Single
	Display Direction	Normal	Normal	Normal	Normal
Color	Backlight	100	100	100	100
	Brightness	0	0	0	0
	Contrast	100	100	100	100
	Temperature	6500 K	6500 K	6500 K	6500 K
	Gamma	2.2	2.2	2.2	2.2
	Color Gamut	sRGB	BT.2020	BT.2020	BT.2020
	Saturation	0	0	0	0
	Hue	0	0	0	0
Signal	Input Color Format	Auto	Auto	Auto	Auto
	YUV Color Matrix	Auto	BT.2020	BT.2020	BT.2020
	Input Range	Auto	Auto	Auto	Limited

### Others

Preferences	Languages		English
	Advanced Setting	On-Screen Logo	On
Custom Key	F1		Off
	F2		Off
	F3		Off
	F4		Off
Key Lock			Unlocked


## 4-2. Pin Specifications

- DC IN terminal



Pin No.	Signal name
1	GND
2	GND
3	F.E
4	DC 48V
5	DC 48V

- DC OUT terminal on the main unit




Pin No.	Signal name
1	GND
2	GND
3	DC 5 V
4	DC 5 V

HIROSE P/N: HR10A-7R-4S(74)

Recommended plug

HIROSE P/N: HR10A-7P-4P(74)

- DC OUT terminal of AC adapter



Pin No.	Signal name
1	GND
2	GND
3	F.E
4	DC 48V
5	DC 48V

# Appendix

## Trademark

The terms HDMI and HDMI High-Definition Multimedia Interface, and the HDMI Logo are trademarks or registered trademarks of HDMI Licensing, LLC in the United States and other countries.

The DisplayPort Compliance Logo and VESA are registered trademarks of the Video Electronics Standards Association.

The SuperSpeed USB Trident Logo is a registered trademark of USB Implementers Forum, Inc.



The USB Power Delivery Trident Logos are trademarks of USB Implementers Forum, Inc.



USB Type-C and USB-C are registered trademarks of USB Implementers Forum, Inc.

DICOM is the registered trademark of the National Electrical Manufacturers Association for its standards publications relating to digital communications of medical information.

Kensington and Microsaver are registered trademarks of ACCO Brands Corporation.

Thunderbolt is a trademark of Intel Corporation in the United States and/or other countries.

Microsoft and Windows are registered trademarks of Microsoft Corporation in the United States and other countries.

Adobe is a registered trademark of Adobe in the United States and other countries.

Apple, macOS, Mac OS, OS X, macOS Sierra, Macintosh and ColorSync are registered trademarks of Apple Inc.

ENERGY STAR is a registered trademark of the United States Environmental Protection Agency in the United States and other countries.

EIZO, the EIZO Logo, ColorEdge, CuratOR, DuraVision, FlexScan, FORIS, RadiCS, RadiForce, RadiNET, Raptor and ScreenManager are registered trademarks of EIZO Corporation in Japan and other countries.

ColorEdge Tablet Controller, ColorNavigator, EcoView NET, EIZO EasyPIX, EIZO Monitor Configurator, EIZO ScreenSlicer, G-Ignition, i-Sound, Quick Color Match, RadiLight, Re/Vue, SafeGuard, Screen Administrator, Screen InStyle, ScreenCleaner, SwitchLink and UniColor Pro are trademarks of EIZO Corporation.

All other company names, product names, and logos are trademarks or registered trademarks of their respective owners.

## License

The bitmap font used for this product is designed by Ricoh Industrial Solutions Inc.

# LIMITED WARRANTY

---

EIZO Corporation (hereinafter referred to as "**EIZO**") and distributors authorized by EIZO (hereinafter referred to as the "**Distributors**") warrant, subject to and in accordance with the terms of this limited warranty (hereinafter referred to as the "**Warranty**"), to the original purchaser (hereinafter referred to as the "**Original Purchaser**") who purchased the product specified in this document (hereinafter referred to as the "**Product**") from EIZO or Distributors, that EIZO and Distributors shall, at their sole discretion, either repair or replace the Product at no charge if the Original Purchaser becomes aware within the Warranty Period (defined below) that the Product malfunctions or is damaged in the course of normal use of the Product in accordance with the description in the instruction manual of the Product (hereinafter referred to as the "**User's Manual**").

The period of this Warranty is three (3) years from the date of purchase of the Product (hereinafter referred to as the "**Warranty Period**"). EIZO and Distributors shall bear no liability or obligation with regard to the Product in relation to the Original Purchaser or any third parties other than as provided under this Warranty.

EIZO and Distributors will cease to hold or store any parts (excluding design parts) of the Product upon expiration of five (5) years after the production of the Product is discontinued. In repairing the Product, EIZO and Distributors will use renewal parts which comply with our QC standards. If the unit cannot be repaired due to its condition or the stockout of a relevant part, EIZO and Distributors may offer the replacement by a product with equivalent performance instead of repairing it.

The Warranty is valid only in the countries or territories where the Distributors are located. The Warranty does not restrict any legal rights of the Original Purchaser.

Notwithstanding any other provision of this Warranty, EIZO and Distributors shall have no obligation under this Warranty whatsoever in any of the cases as set forth below:

- (a) Any defect of the Product caused by freight damage, modification, alteration, abuse, misuse, accident, incorrect installation, disaster, adherent dust, faulty maintenance and/or improper repair by third party other than EIZO and Distributors;
- (b) Any incompatibility of the Product due to possible technical innovations and/or regulations;
- (c) Any deterioration of the sensor, including measurement value of the sensor;
- (d) Any defect of the Product caused by external equipments;
- (e) Any defect of the Product caused by the use under environmental conditions not anticipated by EIZO;
- (f) Any deterioration of the attachments of the Product (e.g. cables, User's Manual, CD-ROM, etc.);
- (g) Any deterioration of the consumables, and/or accessories of the Product (e.g. batteries, remote controller, touch pen, etc.);
- (h) Any exterior deterioration or discoloration of the Product, including that of the surface of the LCD panel, the touch panel and the protect panel;
- (i) Any defect of the Product caused by placement in a location where it may be affected by strong vibrations or shocks;
- (j) Any defect of the Product caused by leaking battery liquid;
- (k) Any deterioration of display performance caused by the deterioration of expendable parts such as the LCD panel and/or backlight, etc. (e.g. changes in brightness, changes in brightness uniformity, changes in color, changes in color uniformity, defects in pixels including burnt pixels, etc.);
- (l) Any deterioration or malfunction of the cooling fan caused by adherent dust.

To obtain service under the Warranty, the Original Purchaser must deliver the Product, freight prepaid, in its original package or other adequate package affording an equal degree of protection, assuming the risk of damage and/or loss in transit, to the local Distributor. The Original Purchaser must present proof of purchase of the Product and the date of such purchase when requesting services under the Warranty.

The Warranty Period for any replaced and/or repaired product under this Warranty shall expire at the end of the original Warranty Period.

**EIZO OR DISTRIBUTORS ARE NOT RESPONSIBLE FOR ANY DAMAGE TO, OR LOSS OF, DATA OR OTHER INFORMATION STORED IN ANY MEDIA OR ANY PART OF ANY PRODUCT RETURNED TO EIZO OR DISTRIBUTORS FOR REPAIR.**

**EIZO AND DISTRIBUTORS MAKE NO FURTHER WARRANTIES, EXPRESSED OR IMPLIED, WITH RESPECT TO, INCLUDING, WITHOUT LIMITATION, THE PRODUCT AND ITS QUALITY, PERFORMANCE, MERCHANTABILITY OR FITNESS FOR ANY PARTICULAR USE. IN NO EVENT SHALL EIZO OR DISTRIBUTORS BE LIABLE FOR ANY INCIDENTAL, INDIRECT, SPECIAL, CONSEQUENTIAL OR OTHER DAMAGE WHATSOEVER (INCLUDING, WITHOUT LIMITATION, DAMAGES FOR LOSS OF PROFIT, BUSINESS INTERRUPTION, LOSS OF BUSINESS INFORMATION, OR ANY OTHER PECUNIARY LOSS) ARISING OUT OF THE USE OR INABILITY TO USE THE PRODUCT OR IN ANY CONNECTION WITH THE PRODUCT, WHETHER BASED ON CONTRACT, TORT, NEGLIGENCE, STRICT LIABILITY OR OTHERWISE, EVEN IF EIZO OR DISTRIBUTORS HAVE BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES. THIS EXCLUSION ALSO INCLUDES ANY LIABILITY WHICH MAY ARISE OUT OF THIRD PARTY CLAIMS AGAINST THE ORIGINAL PURCHASER. THE ESSENCE OF THIS PROVISION IS TO LIMIT THE POTENTIAL LIABILITY OF EIZO AND DISTRIBUTORS ARISING OUT OF THIS LIMITED WARRANTY AND/OR SALES.**

# Recycling Information

## Recycling Information

This product, when disposed of, is supposed to be collected and recycled according to your country's legislation to reduce environmental burden. When you dispose of this product, please contact a distributor or an affiliate in your country.

The contact addressees are listed on the EIZO website below.

[www.eizoglobal.com](http://www.eizoglobal.com)

For recycling information for customers in Switzerland, please refer to the following website.

[www.swico.ch](http://www.swico.ch)

## Informationen zum Thema Recycling

Dieses Produkt muss gemäß den Vorschriften Ihres Landes zur Entlastung der Umwelt recyclet werden. Wenden Sie sich bei der Entsorgung dieses Produkts an einen Verteiler oder eine Tochtergesellschaft in Ihrem Land.

Die Adressen zur Kontaktaufnahme sind auf der unten angegebenen Website von EIZO aufgeführt.

[www.eizoglobal.com](http://www.eizoglobal.com)

Kunden in der Schweiz entnehmen Informationen zum Recycling der folgenden Website:

[www.swico.ch](http://www.swico.ch)

## Informations sur le recyclage

Ce produit doit être jeté aux points de collecte prévus à cet effet et recyclé conformément à la législation de votre pays, afin de réduire l'impact sur l'environnement. Lorsque vous jetez ce produit, veuillez contacter un distributeur ou une société affiliée de votre pays.

Les adresses des distributeurs sont répertoriées sur le site Web EIZO ci-dessous.

[www.eizoglobal.com](http://www.eizoglobal.com)

Pour les clients en Suisse, veuillez consulter le site Web suivant afin d'obtenir des informations sur le recyclage.

[www.swico.ch](http://www.swico.ch)

## Información sobre reciclaje

Este producto debe desecharse y reciclarse según la legislación del país para reducir el impacto medioambiental.

Cuando desee deshacerse de este producto, póngase en contacto con un distribuidor o una filial de su país.

Encontrará las direcciones de contacto en el sitio web de EIZO que se indica a continuación.

[www.eizoglobal.com](http://www.eizoglobal.com)

## Informazioni sul riciclaggio

Per lo smaltimento e il riciclaggio del presente prodotto, attenersi alle normative vigenti nel proprio paese per ridurre l'impatto ambientale. Per lo smaltimento, rivolgersi ad un distributore o un affiliato presenti nel proprio paese.

Gli indirizzi sono elencati nel sito Web EIZO riportato di seguito.

[www.eizoglobal.com](http://www.eizoglobal.com)

Per informazioni sul riciclaggio per i clienti in Svizzera, consultare il sito Web riportato di seguito.

[www.swico.ch](http://www.swico.ch)

## Återvinningsinformation

När denna produkt kasseras ska den hanteras och återvinnas enligt landets föreskrifter för att reducera miljöpåverkan.

När du kasserar produkten ska du kontakta en distributör eller representant i ditt land.

Kontaktadresserna listas på EIZO-webbplatsen nedan.

[www.eizoglobal.com](http://www.eizoglobal.com)

## **Πληροφορίες ανακύκλωσης**

Το προϊόν αυτό, όταν απορρίπτεται, πρέπει να συλλέγεται και να ανακυκλώνεται σύμφωνα με τη νομοθεσία της χώρας σας έτσι ώστε να μην επιβαρύνει το περιβάλλον. Για να απορρίψετε το προϊόν, επικοινωνήστε με έναν αντιπρόσωπο ή μια θυγατρική εταιρεία στη χώρα σας.

Οι διευθύνσεις επικοινωνίας αναγράφονται στην τοποθεσία web της EIZO παρακάτω.  
[www.eizoglobal.com](http://www.eizoglobal.com)

## **Сведения по утилизации**

По истечении срока службы данного продукта его следует принести на сборный пункт и утилизировать в соответствии с действующими предписаниями в вашей стране, чтобы уменьшить вредное воздействие на окружающую среду. Прежде чем выбросить данный продукт, обратитесь к дистрибутору или в местное представительство компании в вашей стране.

Контактные адреса можно найти на веб-узле EIZO.

[www.eizoglobal.com](http://www.eizoglobal.com)

## **Informatie over recycling**

Wanneer u dit product wilt weggooien, moet het uit milieu-overwegingen worden verzameld en gerecycled volgens de betreffende wetgeving van uw land. Wanneer u dit product wilt weggooien, moet u contact opnemen met een distributeur of een partner in uw land.

De contactadressen worden vermeld op de volgende EIZO-website.

[www.eizoglobal.com](http://www.eizoglobal.com)

## **Informação sobre reciclagem**

Este produto, quando o deitar fora, deve ser recolhido e reciclado de acordo com a legislação do seu país para reduzir a poluição. Quando deitar fora este produto, contacte um distribuidor ou uma filial no seu país.

Os endereços de contacto estão listados no website do EIZO, abaixo.

[www.eizoglobal.com](http://www.eizoglobal.com)

## **Oplysninger om genbrug**

Dette produkt forventes ved bortskaffelse at blive indsamlet og genbrugt i overensstemmelse med lovgivningen i dit land for at reducere belastningen af miljøet. Når du bortskaffer denne produkt, skal du kontakte en distributør eller et tilknyttet selskab i dit land.

Adresseerne på kontaktpersonerne er angivet på EIZO's websted nedenfor.

[www.eizoglobal.com](http://www.eizoglobal.com)

## **Kierrätystä koskevia tietoja**

Tuote tulee hävittää kierrättämällä maan lainsäädännön mukaisesti ympäristön kuormittumisen vähentämiseksi. Kun hävität tuotteen, ota yhteyttä jälleenmyyjään tai tytäryhtiöön maassasi.

Yhteystiedot löytyvät EIZOn Internet-sivustolta.

[www.eizoglobal.com](http://www.eizoglobal.com)

## **Wykorzystanie surowców wtórnych**

Ten produkt po zużyciu powinien być zbierany i przetwarzany zgodnie z krajowymi przepisami dotyczącymi ochrony środowiska. Wyrzucając ten produkt, należy skontaktować się z lokalnym dystrybutorem lub partnerem.

Adresy kontaktowe można znaleźć we wskazanej poniżej witrynie internetowej firmy EIZO.

[www.eizoglobal.com](http://www.eizoglobal.com)

## **Informace o recyklaci**

Při likvidaci produktu musí být produkt vyzvednut a recyklován podle zákonů příslušné země, aby nedocházelo k zatěžování životního prostředí. Zbavujete-li se produktu, kontaktujte distributora nebo pobočku ve své zemi.

Kontaktní adresy jsou uvedeny na následující webové stránce společnosti EIZO.

[www.eizoglobal.com](http://www.eizoglobal.com)

## **Ringlussevõtu alane teave**

Keskkonnakoormuse vähendamiseks tuleks kasutatud tooted kokku koguda ja võtta ringlusse vastavalt teie riigi seadustele. Kui kõrvaldate käesoleva toote, võtke palun ühendust turustaja või filialiga oma riigis.

Kontaktisikud on toodud EIZO veebilehel järgmisel aadressil:

[www.eizoglobal.com](http://www.eizoglobal.com)

## **Újrahasznosítási információ**

Jelen terméket, amikor eldobjuk, az illető ország törvényei alapján kell összegyűjteni és újrahasznosítani, hogy csökkentsük a környezet terhelését. Amikor ezt a terméket eldobja, kérjük lépjön kapcsolatba egy országon belüli forgalmazóval vagy társvállalkozással.

A kapcsolat címei az EIZO alábbi weboldalán találhatók felsorolva:

[www.eizoglobal.com](http://www.eizoglobal.com)

## **Podatki o recikliranju**

Ob koncu uporabe odslužen izdelek izročite na zbirno mesto za recikliranje v skladu z okoljevarstveno zakonodajo vaše države. Prosimo, da se pri odstranjevanju izdelka obrnete na lokalnega distributerja ali podružnico.

Kontaktni naslovi so objavljeni na spodaj navedenih spletnih straneh EIZO:

[www.eizoglobal.com](http://www.eizoglobal.com)

## **Informácie o recyklácii**

Pri likvidácii musí byť tento výrobok recyklovaný v súlade s legislatívou vašej krajiny, aby sa znížilo zaťaženie životného prostredia. Keď sa chcete zbaviť tohto výrobku, kontaktujte prosím distribútoru alebo pobočku vo vašej krajine.

Zoznam kontaktných adres je uvedený na nasledovnej webovej stránke firmy EIZO:

[www.eizoglobal.com](http://www.eizoglobal.com)

## **Pārstrādes informācija**

Utilizējot šo produktu, tā savākšana un pārstrāde veicama atbilstoši jūsu valsts likumdošanas prasībām attiecībā uz slodzes uz vidi samazināšanu. Lai veiktu šī produkta utilizāciju, sazinieties ar izplatītāju vai pārstāvniecību jūsu valstī.

Kontaktadreses ir norādītas zemāk minētajā EIZO tīmekļa vietnē.

[www.eizoglobal.com](http://www.eizoglobal.com)

## **Informacija apie grāžinamajį perdirbimą**

Šalinant (išmetant) šiuos gaminius juos reikia surinkti ir perdirbtį grāžinamuoju būdu pagal jūsų šalies teisės aktus, siekiant sumažinti aplinkos teršimą. Kai reikia išmesti šį gaminį, kreipkitės į jūsų šalyje veikiančią gaminių pardavimo atstovybę arba jos filialą.

Kontaktiniai adresatai nurodyti EIZO interneto svetainėje.

[www.eizoglobal.com](http://www.eizoglobal.com)

## **Информация относно рециклиране**

При изхвърлянето на този продукт се предлага събирането и рециклирането му съобразно законите на вашата страна за да се намали замърсяването на околната среда. Когато искате да се освободите от този продукт, моля свържете се с търговския му представител или със съответните органи отговарящи за това във вашата страна.

Данните за връзка с нас са описани на следния Интернет сайт на EIZO:

[www.eizoglobal.com](http://www.eizoglobal.com)

## **Informație referitoare la reciclare**

Acest produs, când debarasat, trebuie colectat și reciclat conform legislației țării respective ca să reducem sarcina mediului. Când se debarasează de acest produs, vă rugăm să contactați un distribuitor sau un afiliat al țării respective. Adresele de contact le găsiți pe pagina de web al EIZO:

[www.eizoglobal.com](http://www.eizoglobal.com)

## معلومات عن إعادة التدوير

عند التخلص من هذا المنتج، من الضروري تجميعه واعادة تدويره وفقاً للقوانين المتبعة في بلدك لتقليل العبء المسلط على البيئة. عندما تخلص من هذا المنتج، يرجى الاتصال بموزع أو طرف متنسب إليه في بلدك. عناوين الاتصال مدرجة في موقع ايزو EIZO ادناه على شبكة الانترنت.

[www.eizoglobal.com](http://www.eizoglobal.com)

## Geri Dönüşüm Bilgisi

Bu ürünün, atılacağı zaman, ülkenizin çevre kirliliğinin azaltılması konusundaki mevzuatına göre toplanması ve yeniden değerlendirilmesi gerekmektedir. Ürünü atacağınız zaman lütfen ülkenizdeki bir distribütör veya ilgili kuruluşla temas geçiniz.

İrtibat adresleri aşağıdaki EIZO web sitesinde verilmiştir.

[www.eizoglobal.com](http://www.eizoglobal.com)



03V60208A1  
IM-EX3242